

NIOC-1RNB

1" Iolite Can-less Round Bullnose

Source: 9W LED
900lm

PRODUCT DESCRIPTION

1" Iolite can-less downlights can be installed in new construction or remodel applications. Deep regressed cone reflectors optimize visual cut-off.

FEATURES

- No housing required - IC Airtight rated
- Easy installation for remodel or new construction applications
- Variety of trim accessories to configure desired appearance
- Quick disconnect allows for extended lengths
- Dedicated CCT or Comfort Dim (warm dim)
- Flood optic, narrow flood and spot optics (included)
- 5-Year limited warranty
- cULus Listed for Wet Locations

SPECIFICATION

Construction: Trims are constructed of heat dissipating, die-cast aluminum. Aluminum die-cast LED module is threaded to fit the trim and transfer heat.

Air Flow Restriction: Luminaire has factory installed gasket to restrict airflow from room into ceiling plenum to <2CFM (cubic feet per minute) in accordance with ASTM 283 airtight requirements.

Clearance: IC rated luminaires are rated for direct contact with insulation (not spray foam insulation), no minimum clearance is required.

Driver Box: Prewired junction box includes 16.5" quick connect wire to LED module for ease of installation. Junction box includes two 1/2" trade size knockouts and snap on cover.

Maximum length between luminaire and driver is 40'. For longer remote driver remote run length, consult factory.

Mounting: No housing is required, two tensions steel spring clips secure luminaire to ceiling. Accommodates ceiling thickness up to 3/4". New construction frame-in kit is available, see accessories.

OPTICS

Each module includes field changeable optics (spot, narrow flood and flood - preinstalled).

ELECTRICAL

Input Voltage: 120VAC

Lumens / Wattage: 900lm / 9W

Color Temperature: 2700K, 3000K, 3500K, 4000K, or Comfort Dim (warm dim)

Color Rendering Index: 90+CRI

Operating Temperature: 0°-30°C

Lifetime: 50,000 hours @ L70

Comfort Dim: Comfort Dim color tunes the temperature from a bright 2900K, to a romantic and comfortable 1900K on a gradual, even curve. Available in 650lm only.

Dimming: Triac or ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab.

Accessories: Luminaire will accommodate (1) hex louver and (1) translucent deco collar or opaque snoot, no accessory holder is required, see accessories page.

LABELS AND LISTINGS

- cULus Listed for Wet Locations
- [5-Year Limited Warranty](#)
- RoHS Compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2025



Type

Project

Catalog No.


Notes

Performance Data

Part Number	Lumens	CCT	Optic
NIOC-1RNBMPW NIOC-1LED940X NJCB-09	927lm	4000K	24° Spot
	899lm	4000K	43° NFL
	887lm	4000K	60° Flood

Delivered lumens will vary depending on CCT, optic and finish

PRODUCT IMAGES & DIMENSIONS



1" Iolite Can-less Round Downlight Trim



MPW
Bright White



WW
Warm White

Item Number

- **NIOC-1RNBMPW** = Bright White Finish
- **NIOC-1RNBWW** = Warm White Finish


1" Iolite Can-less LED Module



Color Temperature

- **NIOC-1LED927X** = 2700K
- **NIOC-1LED930X** = 3000K
- **NIOC-1LED935X** = 3500K
- **NIOC-1LED940X** = 4000K
- **NIOC-1LED9CDX** = Comfort Dim (2900K-1900K)

Driver Box



Wattage

- **NJCB-09** = 9W / 120VAC input / Triac or ELV dimming

Example: **NIOC-1RNBMPW / NIOC-1LED930X / NJCB-09** = 1" Iolite Can-less Bullnose Trim, Bright White finish, 3000K LED Module, 9W Driver Box with 120VAC input; Triac or ELV dimming


Iolite Can-less Accessories

1" Iolite Can-less Round Bullnose

Type	
Project	
Catalog No.	
Notes	

FIELD CHANGEABLE OPTICS

Iolite luminaires include spot, narrow flood and flood optics. Optics can be changed in the field by removing LED module from die-cast trim. Optional frosted optics are also available.



Frosted Optics


NIO-1REFL20FR
NIO-1REFL60FR

40° Optic
60° Optic

Optic assembly includes optional frosted lens.

TRIM ACCESSORIES

Iolite accessories can be added at any point in the design process. Accessories easily install between LED module and die-cast trim. Luminaire will accommodate (1) hex louver and (1) collar accessory, no accessory holder required.



Translucent Decorative Collar

NIO-1AS15(color) 5/8" length
NIO-1AS19(color) 3/4" length
NIO-1AS24(color) 1" length
Color:
AM (amber), BLU (blue), FR (frosted), R (red)

Translucent collars color the aperture with the specified color while producing white general light. Collars are available in different lengths. Use to add interest, create a theme, match a theme or define a space.



Opaque Collar Snoot

NIO-1AS15(color) 5/8" length
NIO-1AS19(color) 3/4" length
NIO-1AS24(color) 1" length
Color:
BLK (black), MPW (bright white), WH (warm white)

Opaque snoot greatly reduces aperture brightness while preserving light output.



Hex Cell Louver

NIO-1HC Black
Hex cell louver subtly reduces aperture brightness by reducing light output by about 20%.

MOUNTING ACCESSORIES

Iolite canless luminaires are ready to be installed out of the box. Additional mounting accessories can be used to assist during installation or extend length between driver box and luminaire.



Quick Connect Extension Cables

NCA-EW-4
NCA-EW-10

4' Cable
10' Cable

Use to extend the length between luminaire and driver box. Can be connected together to create custom lengths. Maximum length between luminaire and driver is 40'. For longer remote driver remote run length, consult factory.



New Construction Frame-In with Collar

NFC-R231

New construction frame-in with collar can be used to assist installing can-less downlights.



Universal New Construction Frame-In

NF-R124

Universal new construction frame-in can be used to assist installing can-less recessed downlighting.


PHOTOMETRICS

1" Iolite Can-less Round Bullnose

Type	
Project	
Catalog No.	
Notes	

Test Information

Test Number: NTR2031R2
 Part Number: NIOC-1RNB40XMPW
 Beam Spread: 24° Spot
 Lumens: 927lm
 Wattage: 9.31W
 Efficacy: 100lpw
 CCT / CRI: 4000K / 90 CRI
 Spacing Criteria (0°-180°): 0.42
 Spacing Criteria (90°-270°): 0.42



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	168fc	1'-8"
6'	74.5fc	2'-6"
8'	41.9fc	3'-5"
10'	26.8fc	4'-2"
12'	18.6fc	5'-1"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	687	74.2
0-40	845	91.2
0-60	909	98.1
0-90	927	100
90-180	0	0
0-180	927	100

Candela Table

Vertical Angles	Candela
0	2682
5	2347
15	996
25	441
35	266
45	47

Test Information

Test Number: NTR2032R2
 Part Number: NIOC-1RNB40XMPW
 Beam Spread: 43° Narrow Flood
 Lumens: 899lm
 Wattage: 9.26W
 Efficacy: 97lpw
 CCT / CRI: 4000K / 90 CRI
 Spacing Criteria (0°-180°): 0.68
 Spacing Criteria (90°-270°): 0.68



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	83.4fc	3'-2"
6'	37.1fc	4'-10"
8'	20.8fc	6'-4"
10'	13.3fc	7'-11"
12'	9.3fc	9'-6"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	629	70
0-40	802	89.2
0-60	874	97.2
0-90	899	100
90-180	0	0
0-180	899	100

Candela Table

Vertical Angles	Candela
0	1334
5	1277
15	943
25	546
35	285
45	49

Test Information

Test Number: NTR2033R2
 Part Number: NIOC-1RNB40XMPW
 Beam Spread: 60° Flood
 Lumens: 887lm
 Wattage: 9.26W
 Efficacy: 96lpw
 CCT / CRI: 4000K / 90 CRI
 Spacing Criteria (0°-180°): 0.9
 Spacing Criteria (90°-270°): 0.9



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	58.7fc	4'-7"
6'	26.1fc	6'-11"
8'	14.7fc	9'-2"
10'	9.4fc	11'-6"
12'	6.5fc	13'-10"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	578	65.1
0-40	783	88.3
0-60	862	97.2
0-90	887	100
90-180	0	0
0-180	887	100

Candela Table

Vertical Angles	Candela
0	940
5	919
15	798
25	590
35	340
45	58

Lumen Output Multipliers

Color Temperature: 2700K (0.89), 3000K (0.91), 3500K (0.98), 4000K (1.00), Comfort Dim (0.72)

Finish Multipliers

Bright White (1.00), Warm White (1.00)