

PRODUCT FEATURES

- This small yet powerful rechargeable lamp fits in just about any spot, great for restaurant dining tables
- Available in modern finishes
- 12-14 hours of battery life, allowing use for extended periods without worrying about running out of power
- 5- hour charging time
- Designed with an integrated 3-step touch-dimmer.

LAMPING

Includes 120-240V 2.4 watts, 220 delivered lumens, 90 CRI 2700K LED module. Built-in three way dimming. Black includes black cable. White includes white cable. Natural Brass includes cream cable. 6 feet of USB C to C cable. Wall charger included.



Matte White



Matte White



Black



Natural Brass

ORDERING INFORMATION

SLTB271	COLOR TEMP	FINISH	LAMP
	27 2700K	B BLACK W MATTE WHITE NB NATURAL BRASS	WALL CHARGER INCLUDED


SLTB271

JOB NAME

NOTES

SPECIFICATIONS

PRIMARY MATERIAL	Aluminum or Brass
SHADE MATERIAL	Aluminum or Brass
NET WEIGHT	1 lbs
HEIGHT	13in
WIDTH	4.3in
LENGTH	4.3in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		220		
WATTS		2.4		
MAX WATTAGE PER BULB		2.4W		
		120V-240V Integrated 3-Step Touch Dimmer		
CCT		2700K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		1 Year		

* Dimming information available at www.techlighting.com/Downloads#dimming
** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	No		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.